

Lastfuß – Loading Foot

LFC / LFD

<p>LFC 500kg F60X 5 ... 500kg</p>	<p>LFD 500kg F60X 5 ... 500kg</p> <p>aus rostbeständigem Edelstahl Made of stainless steel Härte des Elastomer – Rubber tightness: 75 Sh A ± 5</p>
<p>Alle Maße in mm – All dimensions in mm</p>	

<p>LFC 2t F60X 0,5 ... 2t</p>	<p>SB30X 0,5 ... 2t</p>	<p>SK30X 0,3 ... 2t</p>
<p>Alle Maße in mm – All dimensions in mm</p>		

<p>LFC 5t F60X 5t</p>	<p>SK30X 5t</p>	<p>LFD 5t</p> <p>aus rostbeständigem Edelstahl Made of stainless steel Härte des Elastomer – Rubber tightness: 75 Sh A ± 5</p>
<p>Alle Maße in mm – All dimensions in mm</p>		

Technische Daten - Specifications

LFC	für Typ – for Type	SB30X 0,5 ... 2t	SK30X 0,3 ... 2t	SK30X 5t	F60X 5 ... 500kg	F60X 0,5 ... 2t	F60X 5t
Höhenverstellung A - Height adjustment A [mm]		71,5 ... 93,5	83,5 ... 93,5	105 ... 115	51 ... 58	85,5 ... 95,5	106 ... 116
Max. Kippwinkel – Max. angle E [°]		± 10					
Befestigungsmoment – Tighten torque [N·m]		40	40	100	10	40	100
Material - Material		Stahl, vernickelt – Nickel plated steel					
Härte des Elastomer – Rubber tightness		75 Sh A ± 5					